

**Data Sheet**  
**for One Way Vision Film**

<b>Item Code:</b>	OWV153
<b>Description:</b>	It is made of a PVC vinyl substrate. With the top-coated perforation white flex vinyl, it is coated with a removable pressure sensitive acrylic black adhesive and backed with two sided poly coated lay flat white release liner. It allows stunning graphics on one side and clear, unobstructed view through the glass on the other.
<b>Perforation Size:</b>	1.6mm
<b>Perforated Ratio</b>	45%
<b>Film thickness:</b>	140 micron
<b>Adhesive:</b>	Removable pressure sensitive acrylic black adhesive  Between 15°C to 35°C temperature range, the adhesive can be one year removability with no adhesive; residue and it will be not fall off.
<b>Release Paper:</b>	140 ±10g/sqm One side PE and silicon coated wood pulp paper,
<b>Size:</b>	0.98m, 1.27m, 1.35m, 1.52m (width) 50m, 100m (length)
<b>Printing:</b>	Solvent, Eco-solvent, UV inks
<b>Application:</b>	1) Window graphics; 2) Glass curtain wall advertising; 3) Vehicle Graphics; 4) Building glass panels; 5) Glass doors.
<b>Application Temperature:</b>	10°C to 40°C
<b>Storage Condition:</b>	1 year if the temperature 21°C, relative humidity 50%